




REV	DESCRIPTION	DATE	MADE BY	APP'L
2	Tables updated.	27.04.2016	BK	AY

ISOLATOR PROPERTIES

ISOLATOR TYPE	Load Capacity (kg)	Load Capacity (lb)	Outer Spring Color	Inner Spring Color
AH-S-2A-35 *	35	77	White	-
AH-S-2A-60	60	132	Black	-
AH-S-2A-95	95	209	Green	-
AH-S-2A-110 *	110	243	Black	Green
AH-S-2A-145	145	320	Green	Green
AH-S-2A-185	185	408	Yellow	-
AH-S-2A-235 *	235	518	Yellow	Green
AH-S-2A-275	275	606	Blue	-
AH-S-2A-325	325	717	Blue	Green
AH-S-2A-370 *	370	816	Beige	-
AH-S-2A-420	420	926	Beige	Green
AH-S-2A-460 *	460	1014	Red	-
AH-S-2A-550 *	550	1213	Yellow	Blue
AH-S-2A-640	640	1411	Blue	Blue
AH-S-2A-735	735	1621	Beige	Blue
AH-S-1B-825	825	1819	Red	Blue

* Rod can swing 30 degree.

NOTES:

- Specified Load Capacity is the max. allowable load for a single isolator and this value must not be exceeded.
- Isolator must be installed per Installation Instruction 9160.

POD PERFORMANCE OUTLINE DRAWING			AH-S-2A Type Housed Spring Hanger with 2" Deflection		ACREFINE® FIXING & SEISMIC		
PROJECT INFORMATION	CUSTOMER		PROJECT NAME		DRAWING No.	8226	REV
	ENGINEER				DRAWING BY	MMD	
	DATE		LOCATION		DATE	18.02.2010	2
	PROJECT No.				SCALE	NTS	